

VLXV-LED

Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic or optional clear prismatic acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup (36" or 48" only)
- Spring end caps for no visible fasteners
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



Type:	
Job Name:	



Length - 24" - 36" - 48" - 60" - 72"
 Height - 4 1/4"
 Depth - 4 1/4"



ORDERING INFORMATION

Example: VLXV-36-LED-O3C-2-W1-WSA

VLXV

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
24-LED	O2C	18	2420	0-10v	NO	2 3000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
	F1Y	30	3235	TRIAC/ELV	YES	3 3500K		Z1 Satin Bronze		
						4 4000K		Z3 Text Bronze		
36-LED	O3C	27	3630	0-10v	NO			W1 Yolk White		T24 Title 24/JA8 Compliant (F1Y configuration only)
48-LED	O4C	36	4840	0-10v	NO			W2 Gloss White		
60-LED	O5C	45	6050	0-10v	NO			W3 Text White		
72-LED	O6C	54	7260	0-10v	NO			T4 Shimmer Gray		
								M13 Anod Silver		
								T6 Pewter		Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute
								W13 Pearl Beige		
								Optional (See Price List)		
								M17 Brass Powder		



28435 Industry Drive., Valencia, California 91355
 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 www.lightwayind.com • sales@lightwayind.com



Revision: 05/06/2026