

MDJW-7xx-LED

Construction:

- Steel chassis and cage
- Diffuser is .10 extruded white acrylic


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots
- Top and bottom white acrylic lens - standard
- Optional photocell (21) increases fixture depth 1 1/2"
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



	DIM 'A'	M.C.
MDJW-716	16"	8"
MDJW-726	26"	13"
MDJW-738	38"	19"
MDJW-750	50"	25"
MDJW-760	60"	30"



ORDERING INFORMATION

Example: MDJW-726-LED-O2C-4-Z3-WSA

MDJW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
					2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page	
716-LED	O1C	9	1210	0-10v	NO	Optional 3 3500K	W17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		90CRI Consult Factory	
726-LED	O2C	18	2420	0-10v	NO				21 Photocell - See Notes -01 120 volt -02 277 volt	
738-LED	O3C	27	3630	0-10v	NO				Optional Voltage -347V Input voltage to 347v	
750-LED	O4C	36	4840	0-10v	NO				Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

