

CHSC-LED

Construction:

- Steel housing and chassis
- Clear prismatic polycarbonate lens

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard "J-Box" mounting
- Optional photocell - option 21 (specify voltage)
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



CHSC-11

Height - 6 1/2"
Width - 10 1/2"
Depth - 10 1/2"



ORDERING INFORMATION

Example: CHSC-11-LED-F1Q-4-Z1-CPP

CHSC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
11-LED	O2A	12	1600	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	CPP Clear Prismatic Polycarbonate Optional Lens Material (See Price List) WFA White Frsoted Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components T24 Title 24/JA8 Compliant (F1P & F1Q configuration only) 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
	O4A	24	3200	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

