

# CXLC-LED

## Construction:

- Die cast aluminum housing
- Clear prismatic polycarbonate lens

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots for standard "J-Box" mounting
- Optional photocell (21)
- Optional battery backup
- CSA listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Integral Power Supply
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### CXLC-12

Height - 8 3/4"  
 Width - 12 1/2"  
 Depth - 12 1/2"



## ORDERING INFORMATION

**Example: CXLC-12-LED-F1R-4-Z99-CPP**

### CXLC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		Z99 Bronze	CPP Clear Prismatic Polycarbonate	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page  <b>ES</b> Energy Star listed components <b>90CRI</b> Consult Factory <b>21</b> Photocell - Specify voltage 01 - 120 volt 02 - 277 volt  Optional Voltage <b>-347V</b> Input voltage to 347v <b>OCCHFA</b> Concealed Occupancy Sensor See Sensor Resource Sheet  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
12-LED	F1K	13	2115	0-10v	YES	Optional 3 3500K				
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
	O4B	29	4000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

