

TUSB-LED

Construction:

- Steel housing and chassis
- Bottom lens is clear tempered glass

Post:

- (WP) Select tight knotted cedar direct burial post *standard*. Comes 4x6x60" allowing field to define
- (SP) Optional 4" sq steel post 36" tall with square flange base, cover and anchor bolts.

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Optional Photocell - (21) specify voltage 120v or 277v
- Dark Sky compliant
- UL and CUL listed WET location
- 5-Year Warranty on LED Components
- **Companion Wall Fixture - TUSW**



TUSB-8

Height - 7"
Width - 8 1/4"
Depth - 8 3/8"

Type:	
Job Name:	



ORDERING INFORMATION

Example: TUSB-8-LED-O1A-4-W2-CEG-WP-21-01

TUSB

Size	LED				Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
8-LED	O1A	6	800	0-10v	NO	2 3000K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	CEG Clear Tempered Glass	WP Cedar Post (Standard) SP Steel Post (Optional See Price list) <i>Finish to match fixture</i> DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 42 All Aluminum Construction 21 Photocell - <i>See Notes</i> -01 120 volt -02 277 volt ES Energy Star listed components 90CRI Consult Factory
	O2A	12	1600	0-10v	NO				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

