

SFNW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SFNW-12-LED	SFNW-15-LED	SFNW-22-LED
Height - 12"	Height - 14 ½"	Height - 22 ½"
Width - 6"	Width - 8"	Width - 12 ½"
Depth - 4"	Depth - 4"	Depth - 6 ¼"



ORDERING INFORMATION

Example: SFNW-22-LED-O2C-4-Z1-WTP

SFNW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F1H	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K		B1 Satin Black	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES			Z1 Satin Bronze		
	F1P	15	1361	TRIAC/ELV	YES			Z3 Text Bronze		
	F1J	20	2820	0-10v	YES			W1 Yolk White		
15-LED	F1H	9	1400	0-10v	YES			W2 Gloss White	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	90CRI Consult factory ES Energy Star listed components T24 Title 24/JA8 Compliant (F10 & F1P configuration only)
	F1O	10	863	TRIAC/ELV	YES			W3 Text White		
	O2B	15	2000	0-10v	NO			T4 Shimmer Gray		
	F1P	15	1361	TRIAC/ELV	YES			M13 Anod Silver		
	F1J	20	2820	0-10v	YES			T6 Pewter		
22-LED	F1H	9	1400	0-10v	YES			W13 Pearl Beige	16 Bottom Lens	21 Photocell - See Notes -01 120 volt -02 277 volt
	O2C	18	2420	0-10v	NO			Optional (See Price List) M17 Brass Powder		



28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
www.lightwayind.com • sales@lightwayind.com



Revision: 05/05/2023