


MIAW Series



B1 Satin Black



B2 Textured Black



M13 Anodized Silver



T6 Pewter




P9 Brushed Nickel



W13 Pearl Beige



W1 Yolk White



Z1 Satin Bronze



Z3 Textured Bronze




T4 Shimmer Gray



P2 Brushed Aluminum



W3 Textured White



W2 Gloss White



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286
www.lightwayind.com • sales@lightwayind.com



MIAW-600-Series-LED

Construction:

- Steel housing, chassis and cage
- Diffuser UV-stabilized, high impact resistant, DR acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots left and right
- Top and bottom white acrylic lens- standard
- Optional photocell (21) increases fixture depth 1 ½"
- Optional battery backup
- Optional lens cover (ALC) prevents up/down light
- UL and CUL listed **WET** location
 - Build America, Buy America Act Compliant
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



"H" - 18" - 26" - 38"
 "W" - 6 ½"
 "D" - 4"
 "MC" - 9" - 13" - 19"



ORDERING INFORMATION

Example: MIAW-626-LED-O2C-4-B1-WSA

MIAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
						2 3000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)
						3 3500K		B2 Text Black		
						4 4000K		Z1 Satin Bronze		
								Z3 Text Bronze		
								W1 Yolk White		
								W2 Gloss White		
								T4 Shimmer Gray		
								M13 Anod Silver		
								T6 Pewter		
								W13 Pearl Beige		
618-LED	O2A	12	1600	0-10v	NO			Optional (See Price List)	21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt	
626-LED	O2C	18	2420	0-10v	NO			M17 Brass Powder		
638-LED	O3C	27	3630	0-10v	NO			P2 Brushed Alum		
								P9 Brushed Nickel	ALC Aluminum Lens Cover - <i>See Notes</i>	
									39 J-Box with knockouts on all sides	
									Optional Voltage -347V Input voltage to 347v	
									Battery Backup Options (Available with 0-10v only)	
									BB10 10 Watts (1170lm) for 90-Minutes	



28435 Industry Drive., Valencia, California 91355
 800-325-4448 /661-257-0286
 www.lightwayind.com • sales@lightwayind.com



MIAW-900-Series-LED

Construction:

- Steel housing, chassis and cage
- Diffuser is .10" thick extruded white acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots left and right
- Top and bottom white acrylic lens- standard
- Optional photocell (21) increases fixture depth 1 1/2"
- Optional battery backup
- Optional lens cover (ALC) prevents up/down light
- UL and CUL listed **WET** location
 - Build America, Buy America Act Compliant
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



"H" - 20" - 26" - 38"
 "W" - 9 1/2"
 "D" - 5 1/2"
 "MC" - 10" - 13" - 19"



ORDERING INFORMATION

Example: MIAW-926-LED-O4C-4-B1-WSA

MIAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options			
		Watts	Source Lumens	Dimming	Energy Star								
920-LED	O2C	18	2420	0-10v	NO	2 3000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)			
	O4A	24	3200	0-10v	NO	3 3500K		B2 Text Black					
						4 4000K		Z1 Satin Bronze					
926-LED	O2C	18	2420	0-10v	NO			Z3 Text Bronze					21 Photocell - Specify voltage
	O4C	36	4840	0-10v	NO			W1 Yolk White					01 - 120 volt
938-LED	O3C	27	3630	0-10v	NO			W2 Gloss White					02 - 277 volt
								T4 Shimmer Gray					
								M13 Anod Silver					ALC Aluminum Lens Cover - See Notes
								T6 Pewter					
							W13 Pearl Beige						
							Optional (See Price List)			Optional Voltage			
							M17 Brass Powder			-347V Input voltage to 347v			
							P2 Brushed Alum			Battery Backup Options			
							P9 Brushed Nickel			(Available with 0-10v only)			
										BB10 10 Watts (1170lm) for 90-Minutes			



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286
 www.lightwayind.com • sales@lightwayind.com

