

LCSW-LED

Construction:

- Aluminum chassis; accent bar is aluminum
- Diffuser is .10" thick white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Open top and bottom
- Horizontal or vertical mounting
- ADA compliant
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



LCSW-12	LCSW-16	LCSW-26
Height - 12"	Height - 16"	Height - 26"
Width - 9 1/4"	Width - 9 1/4"	Width - 9 1/4"
Depth - 4"	Depth - 4"	Depth - 4"



ORDERING INFORMATION

Example: **LCSW-16-LED-F1P-4-T6-WSA-BSA**

LCSW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	O2A	12	1600	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES			Z1 Satin Bronze		
	F1P	15	1361	TRIAC/ELV	YES			Z3 Text Bronze		
16-LED	O2A	12	1600	0-10v	NO			W1 Yolk White	Accent	ES Energy Star listed components T24 Title 24/JA8 Compliant (F10 & F1P configuration only)
	F1P	15	1361	TRIAC/ELV	YES			W2 Gloss White		
	O2C	18	2420	0-10v	NO			T4 Shimmer Gray		
	F1J	20	2820	0-10v	YES			M13 Anod Silver		
26-LED	O2C	18	2420	0-10v	NO			T6 Pewter	RSA RED Center Lens BSA Blue Center Lens ABA Amber Center Lens GSA Green Center Lens AHA Amber Honey Center Lens WSA White Center Lens	OCCHFB Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet
								Optional (See Price List)		
								M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		
										Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

