

UDSW Series



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com



Revision: 06/04/2024

UDSW-LED

Construction:

- Steel housing and chassis
- Diffuser is .10" thick extruded white acrylic
- Accent rings are extruded aluminum

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots
- Top and bottom clear acrylic lens - standard
- Custom cage styles (X) available
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Cage Style A



Cage Style B

UDSW-9-LED

Height - 9"
Width - 11 1/2"
Depth - 6 1/2"
MC - 3 1/4"

UDSW-11-LED

Height - 11"
Width - 11 1/2"
Depth - 6 1/2"
MC - 5 1/2"



ORDERING INFORMATION

Example: UDSW-9-LED-F1P-4-Z3-WSA

UDSW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
9-LED	O2A	12	1600	0-10v	NO	2 3000K	A	B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)
	O4A	24	3200	0-10v	NO	3 3500K	B	B2 Text Black		
						4 4000K	X	Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige		
11-LED	O2A	12	1600	0-10v	NO			Optional (See Price List)		Battery Backup Options (Available with 0-10v only) (UDSW-11 only) BB10 10 Watts (1170lm) for 90-Minutes
	O4A	24	3200	0-10v	NO			M17 Brass Powder		



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

