

Construction:

- Steel housing and chassis
- Diffuser is extruded white smooth acrylic


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup (see notes)
- Optional Concealed Occupancy Sensor
- **Build America, Buy America Act Compliant**
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Length - 12" - 16" - 24" - 36" - 48"

Height - 5 3/8"

Depth - 3 3/4"



ORDERING INFORMATION

Example: CWPW-36-LED-O3C-4-Z1-WSA

CWPW

						Kelvin	Cage	Finish	Diffuser	Options
Size	LED	Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (see Price List) P9 Brushed Nickel	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) OCCHFA Concealed Occupancy Sensor Battery Backup Options (Available with 0-10v only) Excluding CWPW-12 & CWPW-16 BB10 10 Watts (1170lm) for 90-Minute
12-LED	O1C	9	1210	0-10v	NO					
16-LED	O2A	12	1600	0-10v	NO					
24-LED	O2C	18	2420	0-10v	NO					
	F1Y	30	3235	TRIAC/ELV	YES					
36-LED	O3C	27	3630	0-10v	NO					
48-LED	O4C	36	4840	0-10v	NO					
72-LED	O6C	54	7260	0-10v	NO					
96-LED	O8C	72	9680	0-10v	NO					

