

JPCW-LED

Construction:

- Steel top, bottom and rings
- Diffuser is .080" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic
- Optional glass lenses are .125" thick

Light Source:

- LED
- Dimming to 10% **Included**

Notes:


- Integral mounting plate for standard "J-Box"
- Mounting orientation is downward
- Optional photocell attaches to wall mounting bracket, specify 120v or 277v
- Optional battery backup increase depth 1 1/2"
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

JPCW

Height - 12 1/2"

Width - 6 1/2"

Depth - 8 1/2"



Type:

Job Name:



ORDERING INFORMATION

Example: JPCW-LED-12-F2B-4-Z3-AHG

JPCW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F2B	12	1180	0-10v	NO	2 3000K		B1 Satin Black	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v)
12-LED	F10	10	863	TRIAC/ELV	YES	4 4000K		B2 Text Black		DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
						Optional		Z1 Satin Bronze	Optional Lens Material (see Price List)	90CRI Consult Factory
						3 3500K		Z3 Text Bronze	AHA Amber Honey Alabaster	ES Energy Star listed components
								W1 Yolk White	BAA Beige Alabaster	21 Photocell - See Notes
								W2 Gloss White	OAA Opal Alabaster	-01 120 volt
								T4 Shimmer Gray	AHG Amber Honey Glass	-02 277 volt
								M13 Anod Silver	CSG Clear Seedy Glass	Optional Voltage
								T6 Pewter		-347V Input voltage to 347v
								W13 Pearl Beige		
								Optional (See Price List)		
								M17 Brass Powder		Battery Backup Options (Available with 0-10v only)
										BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com



Revision: 06/20/2025