

RCCW-LED

Construction:

- Aluminum housing and chassis
- Window lens are white textured acrylic, optional alabaster acrylic or custom patterns
- Open top – see Notes for top lens

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for mounting to standard J-Box
- Open top (standard configuration)
- Optional perforated cover (-TL)
- Custom lens patterns available as option (XA)
- Custom cage styles available
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



RCCW-9

Height - 9"
Width - 9"
Depth - 4"

RCCW-14

Height - 9"
Width - 14"
Depth - 4"



ORDERING INFORMATION

Example: RCCW-9-LED-F1H-4-W2-XA

RCCW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
9-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTA White Textured Acrylic	DIM LED dimming driver (0 - 10v)
14-LED	O2C	18	2420	0-10v	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder	Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster XA Custom Patterns	TL Top Cover - (See Notes) 90CRI Consult Factory
										Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286
www.lightwayind.com • sales@lightwayind.com

