

NDTW-LED

Construction:

- Steel housing and chassis
- Bottom lens, see below

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate
- Optional photocell (21)
- Optional all aluminum construction (painted finishes only)
- Dark sky compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



NDTW-14

Height - 14"

Width - 24"

Depth - 15"



ORDERING INFORMATION

Example: **NDTW-14-LED-O1M-4-T4-CEG**

NDTW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
14-LED	O2A	12	1600	0-10v	NO	2 3000K 3 3500K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic CSA Clear Smooth Acrylic WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page 21 Photocell - See Notes -01 120 volt -02 277 volt 42 All Aluminum Construction T24 Title 24/JA8 Compliant Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	O1M	15	2050	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

