

# VECW-LED

## Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate
- Optional translucent bonded linen material

## Light Source:


- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup – hardware included
- Custom cage styles available
- Open top and bottom for up and down light
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components




WHITE LINEN (WLA)



RAPID LINEN (RTA)



SABLE LINEN (SLA)



Type:	
Job Name:	



## VECW-12

Height - 11 3/8"

Width - 12"

Depth - 4"



## ORDERING INFORMATION

Example: VECW-12-LED-F1P-4-Z3-WTP

### VECW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F1H	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES			Optional Lens Material (see Price List)		ES Energy Star listed components
	O2A	12	1600	0-10v	NO			WLA White Linen Acrylic RTA Rapid Textured Acrylic SLA Sable Linen Acrylic		T24 Title 24/JA8 Compliant (F10 & F1P configuration only)
	F1P	15	1361	TRIAC/ELV	YES			Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel		OCCHFB Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet
<p><b>Battery Backup Options</b> (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes</p>										



28435 Industry Drive., Valencia, California 91355  
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
www.lightwayind.com • sales@lightwayind.com

