

# CLPC-LED

## Construction:

- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring (14" & 19" only)
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

|           |  |
|-----------|--|
| Type:     |  |
| Job Name: |  |



**CLPC-11-LED**  
Height - 3"  
Diameter - 11"

**CLPC-14-LED**  
Height - 3 1/2"  
w/ext ring - 5 1/4"  
Diameter - 14"

**CLPC-19-LED**  
Height - 3 3/8"  
w/ext ring - 5 1/4"  
Diameter - 19"



## ORDERING INFORMATION

Example: CLPC-14-LED-F1Q-4-W2-WSA-ES

## CLPC

| Size          | LED        |       |               |           |             | Kelvin                        | Cage | Finish                | Diffuser  | Options   |
|---------------|------------|-------|---------------|-----------|-------------|-------------------------------|------|-----------------------|---|---|
|               |            | Watts | Source Lumens | Dimming   | Energy Star |                               |      |                       |   |   |
| <b>11-LED</b> | <b>F1L</b> | 9     | 1400          | 0-10v     | YES         | 2 3000K<br>3 3500K<br>4 4000K |      | <b>W2</b> Gloss White | <b>WSA</b> White Smooth Acrylic<br><br><b>Optional Lens Material</b><br>(see Price List)<br><b>WSAHE</b> White Smooth Acrylic High Efficiency | <b>DIM</b> LED dimming driver (0 - 10v)<br><b>DIMLD</b> Line Voltage /TRIAC/ELV/120v<br>See Resource Page<br><br><b>EXT</b> Extended housing (14" & 19" only)<br>(adds 2 inches /match BB10)<br><b>42</b> Aluminum Pan (11" & 14" only)<br><b>ES</b> Energy Star listed components<br><b>T24</b> Title 24/JA8 Compliant<br>(F10, F1P & F1Q configuration only)<br><b>OCCHFA</b> Concealed Occupancy Sensor<br>See Sensor Resource Sheet<br><br><b>Battery Backup Options</b><br>(Requires 1 3/4" extension ring)<br>(Available with 0-10v only)<br><b>CLPC-14 and 19 only</b><br><b>BB10</b> 10 Watts (1170lm) for 90-Minutes |
|               | <b>F1O</b> | 10    | 863           | TRIAC/ELV | YES         |                               |      |                       |   |   |
|               | <b>F1P</b> | 15    | 1361          | TRIAC/ELV | YES         |                               |      |                       |   |   |
| <b>14-LED</b> | <b>F1K</b> | 13    | 2115          | 0-10v     | YES         |                               |      |                       |   |   |
|               | <b>F1P</b> | 15    | 1361          | TRIAC/ELV | YES         |                               |      |                       |   |   |
|               | <b>F1Q</b> | 23    | 2057          | TRIAC/ELV | YES         |                               |      |                       |   |   |
| <b>19-LED</b> | <b>L1A</b> | 36    | 4000          | 0-10v     | NO          |                               |      |                       |   |   |



28435 Industry Drive., Valencia, California 91355  
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
www.lightwayind.com • sales@lightwayind.com

