

# NEFW-LED

## Construction:


- Housing and chassis is steel
- Diffuser is vandal resistant acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Integral mounting plate; Hardware include
- Mounts on a 2x4 jbox or 4" square post
- Optional two color choice of the frame and cover
- Optional battery backup available on fixtures 426 & larger
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components



	DIM 'A'	Mount-Center
NEFW-413	13"	6.5"
NEFW-426	26"	13"
NEFW-438	38"	19"
NEFW-450	50"	25"
NEFW-460	60"	30"

Type:	
Job Name:	



## ORDERING INFORMATION

Example: NEFW-438-LED-O3C-3-Z3-Z3-DIM

### NEFW

Size	LED					Kelvin	Cage	Finish	Front Deco Finish	Options
		Watts	Source Lumens	Dimming	Energy Star					
413-LED	O1C	9	1210	0-10v	NO	2 3000K 3 3500K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige  Optional (See Price List) M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige  Optional (See Price List) M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	DIM LED dimming driver (0 - 10v) Dimming to 10% <b>(Included)</b>  42 All Aluminum Construction     <b>Battery Backup Options</b> Available <b>(426 &amp; Larger)</b> <b>BB10</b> Battery backup unit providing 10 Watts (1170lm) for 90-Minute	
426-LED	O2C	18	2420	0-10v	NO					
438-LED	O3C	27	3630	0-10v	NO					
450-LED	O4C	36	4840	0-10v	NO					
460-LED	O5C	45	6050	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

