

PCLC-LED

Construction:

- Steel pan and rings
- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring
- Ceiling or Wall Mount
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PCLC-12 Height - 3" w/ext ring - 5 1/4" Diameter - 12"	PCLC-15 Height - 3" w/ext ring - 5 1/4" Diameter - 15"	PCLC-21 Height - 3 3/8" w/ext ring - 5 1/4" Diameter - 21 1/4"
--	--	--



ORDERING INFORMATION

Example: PCLC-15-LED-2R-F1P-4-T6-WSA-DIM

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
PCLC-12-2R-LED	F1L	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K	T6 Pewter	WSA White Smooth Acrylic Optional Lens Material (see Price List) WSAHE White Smooth Acrylic High Efficiency	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components T24 Title 24/JA8 Compliant (F10, F1P & F1Q configuration only) OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Battery Backup Options (Requires 1 3/4" extension ring) (Available with 0-10v only) PCLC-15 and 21 only BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES		W2 Gloss White		
	F1P	15	1361	TRIAC/ELV	YES		Z1 Satin Bronze Z3 Text Bronze W1 Yolk W3 Text White		
PCLC-15-2R-LED	F1K	13	2115	0-10v	YES		B1 Satin Black		
	F1P	15	1361	TRIAC/ELV	YES		B2 Text Black		
	F1Q	23	2057	TRIAC/ELV	YES		T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige		
PCLC-21-2R-LED	L1A	36	4000	0-10v	NO				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 www.lightwayind.com • sales@lightwayind.com

