

# PDLH-LED

## Construction:

- Steel housing and chassis
- Bottom lens is white frosted acrylic
- Field adjustable aircraft cable

## Light Source:

- LED
- Dimming to 10% **Included**


## Notes:

- Mounts to standard junction box
- Optional battery backup
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



	PDLH-24	PDLH-36	PDLH-47
A	24"	36"	47"
B	3"	3"	3"
C	2 1/2"	2 1/2"	2 1/2"
D	12"	24"	35"
OAH	6 - 24"	6 - 24"	6 - 24"



## ORDERING INFORMATION

Example: **PDLH-36-LED-O3C-4-T4-WSA**

### PDLH

Size	LED					Kelvin	Cage	Finish	Diffuser	Suspension/Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder <b>M16</b> Antique Brass <b>P2</b> Brushed Alum <b>P9</b> Brushed Nickel	WFA White Frosted Acrylic	<b>(Suspension Systems)</b> <b>2AC</b> - Aircraft Cable w/ <b>WSJ</b> - White "SJ" Cord <b>BSJ</b> - Black "SJ" Cord <b>GSJ</b> - Gray "SJ" Cord  <b>DIM</b> LED dimming driver (0 - 10v)  <b>Battery Backup Options</b> Available in 36" and 47" only <b>BB08</b> Battery backup unit providing 8 Watts (1080lm) for 90-Minute
36-LED	O3C	27	3630	0-10v	NO					
47-LED	O4C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

