

BUAW-LED

Construction:

- Steel housing and chassis
- Optional Aluminum construction

Light Source:

- LED
- Dimming to 10% **Included**


Notes:

- Universal mounting plate
- Up/Down Light
- Optional Aluminum construction
- ADA compliant
- UL and CUL listed **WET** location
- LED Components

Type:	
Job Name:	



BUAW-"A" Height- 15" or 31" or 46"
Width: 4 3/4"



ORDERING INFORMATION

Example: BUAW-31-LED-F2B-4-Z1

BUAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		DIM LED dimming driver (0 - 10v) 42 All Aluminum Construction
15-LED	F2B	12	1180	0-10v	NO					
31-LED	F2B	12	1180	0-10v	NO					
46-LED	F2B	12	1180	0-10v	NO					
<ul style="list-style-type: none"> • 50% Up / 50% Down 										



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com

