

TUXW-LED

Construction:

- Steel housing and chassis
- Bottom lens is clear smooth acrylic; optional white frosted acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Universal Mounting Pattern and hardware include
- Optional all aluminum construction (option 42)
- ADA compliant
- Dark Sky compliant
- BUG Rating: B1-U0-G0
- UL and CUL listed **WET** location
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



TUXW-15-LED

Height - 5"
Width - 15"
Depth - 4"



ORDERING INFORMATION

Example: TUXW-15-LED-01C-4-W2-WFA

TUXW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	1 2700K 2 3000K 3 3500K 4 4000K 5 5000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M17 Brass Powder Optional (See Price List) P9 Brushed Nickel	CSA Clear Smooth Acrylic WFA White Frost Acrylic	DIM LED dimming driver (0 - 10v) 42 All Aluminum Construction
15-LED	01C14	14	1880	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

