

NERW-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white textured acrylic
- Accent rings are extruded aluminum

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Open top and bottom
- ADA compliant
- Optional battery backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



NERW-14

Height - 14"
Width - 12"
Depth - 4"



ORDERING INFORMATION

Example: **NERW-14-LED-F1H-4-T6-WTP**

NERW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
14-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze Optional Finishes (see Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	F1O	10	1065	TRIAC/ELV	YES					
	F1P	15	1724	TRIAC/ELV	YES					
	F1J	20	2820	0-10v	YES					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

