

CPLP-LED

Construction:

- Die cast aluminum body and finial
- Diffuser is .080" thick white textured polycarbonate or optional white smooth polycarbonate

Light Source:

- LED

Notes:

- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



CPLP-23-LED

Height - 19 1/2"

Width - 12"

Depth - 12"



ORDERING INFORMATION

Example: CPLP-23-LED-O4A-4-B1-WTP

CPLP

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K				
23-LED	O4A	24	3200	0-10v	NO			WTP White Textured Polycarbonate	Pole Options (see supplemental spec sheet on website and price list)	
	O4C50	50	6015	0-10v	NO			Optional Lens Material (See Price List)		
	1E26		0	TRIAC/ELV	NO			AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate		
							W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder			



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

