

SRLW-LED

Construction:

- Aluminum housing and chassis
- Diffuser is white textured or optional white smooth polycarbonate.
- Optional alabaster lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Keyhole slots right and left
- Custom cage styles available
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SRLW-10-LED

Height - 10"
Width - 11"
Depth - 6"



ORDERING INFORMATION

Example: SRLW-10-LED-F1H-4-B1-WTP

SRLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder	WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) ES Energy Star listed components 16 Bottom Lens 21 Photocell - See Notes -01 120 volt -02 277 volt
10-LED	F1H	9	1400	0-10v	YES					



28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
Ewww.lightwayind.com • sales@lightwayind.com

