

# BPSW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth or textured polycarbonate.
- Optional amber, beige or opal alabaster acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Integral mounting plate for standard "J-Box"
- Bottom of fixture is open; optional clear or white acrylic bottom lens or solid bottom cover (no down light)
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



<b>BPSW-12</b>	<b>BPSW-16</b>	<b>BPSW-22</b>
Height - 12"	Height - 16"	Height - 24"
Width - 8"	Width - 8"	Width - 8"
Depth -14"	Depth -14"	Depth - 14"



## ORDERING INFORMATION

**Example: BPSW-16-LED-O2B-4-Z3-WSP-CBL**

### BPSW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>M13</b> Anod Silver <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>W1</b> Yolk <b>W2</b> Gloss White <b>W3</b> Text White <b>W13</b> Pearl Beige <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze	<b>WTP</b> White Textured Polycarbonate  <b>WSP</b> White Smooth polycarbonate  <b>Optional Lens Material</b> (see Price List) <b>AHA</b> Amber Honey Alabaster <b>BAA</b> Beige Alabaster <b>OAA</b> Opal Alabaster	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% <b>(Included)</b>  <b>CBL</b> Clear Bottom Lens <b>WBL</b> White Acrylic Bottom Lens <b>SSB</b> Solid Bottom Cover <b>Z1</b> Photocell - <i>See Notes</i> -01 120 volt -02 277 volt
<b>12-LED</b>	<b>O2B</b>	15	2000	0-10v	NO	<b>Optional</b> 3 3500K				
<b>16-LED</b>	<b>O2B</b>	15	2000	0-10v	NO					
<b>22-LED</b>	<b>O4B</b>	29	4000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

