

BPRW-LED

Construction:

- Steel top, bottom and rings
- Cylinder is .125" thick white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**


Notes:

- Integral mounting plate for standard "J-Box"
- Standard mounting orientation is upward
- For optional downward mounting consult factory
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components


Type:	
Job Name:	



BPRW- 16 - 20 - 25
 Height - 15" - 19" - 24"
 Width - 7 1/4" 8 1/2" 10"
 Depth - 9 3/4" 11" 13"



Upward Mounting
(MU)



Downward Mounting
(MD)



ORDERING INFORMATION

Example: **BPRW-16-LED-O4C-4-Z3-WSA-MU**

BPRW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options	
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W1 Yolk W2 Gloss White W3 Text White W13 Pearl Beige Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)	
16-LED	O4C	36	4840	0-10v	NO	Optional 3 3500K				MU Mounted Upward (Standard) MD Mounted Downward (Consult Factory for Lamping Options)	
	1E26		0	TRIAC/ELV	NO						
20-LED	O4C	36	4840	0-10v	NO						
25-LED	O8A	48	6400	0-10v	NO						



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

