

HWXW-LED

Type:	
Job Name:	

Construction:

- Aluminum housing and chassis
- Diffuser is .080" thick white textured polycarbonate
- Optional diffuser is clear prismatic acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



HWXW-9-LED

Height - 9 1/4"

Width - 5"

Depth - 4"



ORDERING INFORMATION

Example: HWXW-9-LED-F10-4-B1-CPA

HWXW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate Optional Lens Material (see Price List) CPA Clear Prismatic Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory
9-LED	F10	10	1065	TRIAC/ELV	YES	Optional 3 3500K		Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		
	F1C	10	1518	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com



Revision: 01/08/2020