

LBLW-LED

Construction:

- Steel housing and chassis
- Diffuser is Translucent Bonded Linen Material available in a variety of color options

Light Source:

- LED
- Dimming to 10% **Included**

Notes:


- Mounts to standard J-box
- Custom cage styles available
- ADA compliant
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components




White Linen (WLA)



Chocolate Textured Acrylic (CTA)



Rapid Textured (RTA)



Black Textured Acrylic (BTA)

LBLW-15

Height - 15"
Width - 6.5"
Depth - 3.5"

LBLW-27

Height - 27"
Width - 6.5"
Depth - 3.5"

Type:	
Job Name:	



ORDERING INFORMATION

Example: LBLW-27-LED-O2C-3-B1-WLA

LBLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WLA White Linen Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
15-LED	O1C13	9	1400	0-10v	NO	Optional 3 3500K	Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	RTA Rapid Textured Acrylic BTA Black Textured Acrylic CTA Chocolate Textured Acrylic	90CRI Consult Factory OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i>	
27-LED	O2C	18	2420	0-10v	NO					
	O2C32	32	3654	0-10v	NO					Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

