

### Construction:

- Steel top, bottom and rings
- Diffuser is white textured polycarbonate
- Optional alabaster lenses are acrylic


### Lamps:

- LED
- Dimming to 10%

### Notes:

- Integral mounting plate for standard "J-Box"
- Mounting orientation is downward
- Optional photocell attaches to wall mounting bracket, specify 120v or 277v
- Optional battery backup, increases depth 1 1/2"
- UL and CUL listed **WET** location
- LED Components

- Replaceable Module
- CRI > 90
- Universal 120/277 volt standard
- 5-Year Warranty on LED Components



Type:	
Job Name:	



## ORDERING INFORMATION

Example: JPOW-LED-12-F2B-3-Z1-AHG

### JPOW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F2B	12	1180	0-10v	NO	2 3000K 3 3500K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>W3</b> Text White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder	<b>WTP</b> White Textured Polycarbonate  <b>Optional Lens Material</b> (see Price List) <b>AHA</b> Amber Honey Alabaster <b>BAA</b> Beige Alabaster <b>OAA</b> Opal Alabaster	<b>DIM</b> LED dimming driver (0 - 10v)  <b>Z1</b> Photocell - Specify voltage 01 - 120 volt 02 - 277 volt  Optional Voltage <b>-347V</b> Input voltage to 347v  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355  
 800-325-4448 / 661-257-0286  
 www.lightwayind.com • sales@lightwayind.com

