

# THOW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .10" thick extruded white acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

Type:	
Job Name:	



### THOW-16-LED

Height - 16"  
Width - 7 1/8"  
Depth - 4"

### THOW-24-LED

Height - 24"  
Width - 7 1/8"  
Depth - 4"



## ORDERING INFORMATION

Example: THOW-16-LED-02C-4-B1-WSA

## THOW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		<b>B1</b> Satin Black <b>M13</b> Anod Silver <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>W2</b> Gloss White <b>W1</b> Yolk White <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>M17</b> Metallic Brass <b>P1</b> Chrome* <b>P2</b> Brushed Alum	WSA White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v)
16-LED	O2C	18	2420	0-10v	NO					
24-LED	O2C	18	2420	0-10v	NO					
<p style="text-align: right;">                     Optional Voltage                      -347V Input voltage to 347v   <b>Battery Backup Options</b>                      (Available with 0-10v only)  <b>BB10</b> 10 Watts (1170lm) for 90-Minutes                 </p>										



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

