

# DELW-LED

## Construction:

- Steel housing and aluminum chassis
- Diffuser is .10" thick extruded white acrylic

## Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

## Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

Type:	
Job Name:	



WALL  
CEILING  
PENDANT  
OUTDOOR

### DELW-16-LED

Height - 16"  
Width - 7 1/8"  
Depth - 4"

### DELW-24-LED

Height - 24"  
Width - 7 1/8"  
Depth - 4"



## ORDERING INFORMATION

**Example: DELW-16-LED-U-21W-3-B1-WSA**

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
<b>DELW-16-LED</b>		<b>U</b> 120-277v	<b>14w</b> LED / 1600lm (114 lm per watt)  <b>21w</b> LED / 2450lm (117 lm per watt)	<b>2</b> 3000K <b>4</b> 4000K  <b>Optional</b> <b>3</b> 3500K	<b>B1</b> Satin Black <b>W1</b> Yolk <b>W2</b> Gloss White <b>P0</b> Polished Brass* <b>P1</b> Chrome* <b>P2</b> Brushed Alum	<b>WSA</b> White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% ( <b>Included</b> )
<b>DELW-24-LED</b>			<b>18w</b> LED / 2000lm (111 lm per watt)  <b>21w</b> LED / 2450lm (117 lm per watt)		<b>Optional Finishes</b> (see Price List) <b>M13</b> Anod Silver <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>W13</b> Pearl Beige <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze		<b>Battery Backup Options</b> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes

\* Interior Use Only



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

