

FWXA-LED

Construction:

- Aluminum housing and chassis
- Diffuser is Clear Smooth Acrylic or optional White Frosted Acrylic

Light Source:

- LED
- Dimming to 10%

Notes:

- ½" NPT knuckle mounts to junction box or ground fitter
- Optional Photocell (21) – specify voltage 120v or 277v
- FWXA-5 and 15 come standard with (1) knuckle – use option 2K for additional knuckle
- Optional Extension arms to match finish
- UL and CUL listed **WET** location
- Build America, Buy America Act Compliant
- LED Components
 - Replaceable Module
 - CRI > 90
 - Voltage 120 - 208 - 240 - 277
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



FWXA-5	FWXA-15
Height - 5"	Height - 5"
Width - 9¼"	Width - 14¼"
Depth - 7"	Depth - 7"



ORDERING INFORMATION

Example: FWXA-5-LED-O2A-4-P3-CSA-24

FWXA

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K 5 5000K		P3 Clear Anodized Aluminum Optional <i>(See Price List)</i>	WFA White Frosted Acrylic CSA Clear Smooth Acrylic	DIM LED dimming driver (0 - 10v)
5-LED	O1A	6	800	0-10v	NO					
	O2A	12	1600	0-10v	NO					
15-LED	O2A	12	1600	0-10v	NO					21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt
							W1 Yolk W2 Gloss White W3 Text White B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige			24 24" Extension Arms 84 Ground Fitter TM Trunnion Mount 2K (2) Knuckles FH Fixed Hood



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

