

BDYW-LED

Construction:

- Cast aluminum housing
- Aluminum reflector
- Clear tempered glass lens

Lamps:

- Lamps **INCLUDED**

Notes:

- Wall mounting bracket attaches to 4" recessed outlet box
- Optional Photocell
- Optional Battery backup
- Dark Sky compliant
- UL and CUL listed WET location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



BDYW-7

Height - 9 1/8"
 Width - 18 1/8"
 Depth - 9 1/8"



ORDERING INFORMATION

Example: **BDYW-7-LED-O2C-2-Z99-CEG**

BDYW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	CEG Clear Tempered Glass	DIM LED dimming driver (0 - 10v) 21 Photocell - <i>See Notes</i> -01 120 volt -02 277 volt 90CRI Consult Factory Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutess
7-LED	O2C	18	2420	0-10v	NO	Optional 3 3500K				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com



Revision: 02/06/2025