

VALW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



VALW-13-LED

Height - 13"
Width - 7 1/4"
Depth - 4"

VALW-15-LED

Height - 14 3/4"
Width - 8 1/4"
Depth - 4"

VALW-18

Height - 19 5/8"
Width - 11"
Depth - 6"



ORDERING INFORMATION

Example: VALW-18-LED-O2C-4-Z1-WTP

VALW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K				
13-LED	F1O	10	863	TRIAC/ELV	YES		B1 Satin Black B2 Text Black	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page T24 Title 24/JA8 Compliant (F10 & F1P configuration only) ES Energy Star listed components 16 Bottom Lens 21 Photocell - See Notes -01 120 volt -02 277 volt Battery Backup Options (Available with O2B & O2C only) (VALW-15 & 18 only) BB10 10 Watts (1170lm) for 90-Minutes	
	F1P	15	1361	TRIAC/ELV	YES		Z1 Satin Bronze Z3 Text Bronze			
	F1H	9	1400	0-10v	YES		W1 Yolk White W2 Gloss White	Optional Lens Material (See Price List)		
	F1J	20	2820	0-10v	YES		W3 Text White W4 Shimmer Gray	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate		
15-LED	F1H	9	1400	0-10v	YES		M13 Anod Silver T6 Pewter			
	F1P	15	1361	TRIAC/ELV	YES		W13 Pearl Beige			
	O2B	15	2000	0-10v	NO		Optional (See Price List)			
18-LED	F1H	9	1400	0-10v	YES		M17 Brass Powder M16 Antique Brass			
	O2C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

