

# CCLC-LED

## Construction:

- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring (14" & 19" only)
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



<b>CCLC-11-LED</b>	<b>CCLC-14-LED</b>	<b>CCLC-19-LED</b>
Height - 3"	Height - 3 1/2"	Height - 3 3/8"
Diameter - 11"	w/ext ring - 5 1/4"	w/ext ring - 5 1/4"
	Diameter - 14"	Diameter - 19"



## ORDERING INFORMATION

Example: CCLC-14-LED-F1Q-4-W2-WSA-ES

## CCLC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
<b>11-LED</b>	<b>F1L</b>	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K		<b>W2</b> Gloss White	<b>WSA</b> White Smooth Acrylic  <b>Optional Lens Material</b> (see Price List) <b>WSAHE</b> White Smooth Acrylic High Efficiency	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page  <b>ES</b> Energy Star listed components <b>T24</b> Title 24/JA8 Compliant (F10, F1P & F1Q configuration only)  <b>OCCHFA</b> Concealed Occupancy Sensor See Sensor Resource Sheet  <b>42</b> Aluminum Pan (11" & 14" only)  <b>Battery Backup Options</b> (Requires 1 3/4" extension ring) (Available with 0-10v only) <b>CCLC-14 and 19 only</b> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
	<b>F1O</b>	10	863	TRIAC/ELV	YES					
	<b>F1P</b>	15	1361	TRIAC/ELV	YES					
<b>14-LED</b>	<b>F1K</b>	13	2115	0-10v	YES					
	<b>F1P</b>	15	1361	TRIAC/ELV	YES					
	<b>F1Q</b>	23	2057	TRIAC/ELV	YES					
<b>19-LED</b>	<b>L1A</b>	36	4000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
www.lightwayind.com • sales@lightwayind.com

