

CLPC-LED

Construction:

- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring (14" & 19" only)
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

| | |
|-----------|--|
| Type: | |
| Job Name: | |



| | | |
|--------------------|---------------------|---------------------|
| CLPC-11-LED | CLPC-14-LED | CLPC-19-LED |
| Height - 3" | Height - 3 1/2" | Height - 3 3/8" |
| Diameter - 11" | w/ext ring - 5 1/4" | w/ext ring - 5 1/4" |
| | Diameter - 14" | Diameter - 19" |



ORDERING INFORMATION

Example: CLPC-14-LED-F1Q-4-W2-WSA-ES

CLPC

| Size | LED | | | | | Kelvin | Cage | Finish | Diffuser | Options |
|---------------|------------|-------|---------------|-----------|-------------|-------------------------------|------|-----------------------|---|---|
| | | Watts | Source Lumens | Dimming | Energy Star | | | | | |
| 11-LED | F1L | 9 | 1400 | 0-10v | YES | 2 3000K 3 3500K 4 4000K | | W2 Gloss White | WSA White Smooth Acrylic | DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page |
| | F1O | 10 | 863 | TRIAC/ELV | YES | | | | | |
| | F1P | 15 | 1361 | TRIAC/ELV | YES | | | | | |
| 14-LED | F1K | 13 | 2115 | 0-10v | YES | | | | Optional Lens Material (see Price List) | EXT Extended housing (14" & 19" only) (adds 2 inches /match BB10) |
| | F1P | 15 | 1361 | TRIAC/ELV | YES | | | | | |
| | F1Q | 23 | 2057 | TRIAC/ELV | YES | | | | | |
| 19-LED | L1A | 36 | 4000 | 0-10v | NO | | | | WSAHE White Smooth Acrylic High Efficiency | 42 Aluminum Pan (11" & 14" only) ES Energy Star listed components T24 Title 24/JA8 Compliant (F1O, F1P & F1Q configuration only) OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet |
| | | | | | | | | | | Battery Backup Options (Requires 1 3/4" extension ring) (Available with 0-10v only) CLPC-14 and 19 only BB10 10 Watts (1170lm) for 90-Minutes |



28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
www.lightwayind.com • sales@lightwayind.com

