LCAC-LED

Construction:

- Bottom Diffuser is a White Textured Acrylic
- Side Diffuser is a Translucent Bonded Linen Material with a with a variety of color options.
- Housing are steel with a powder coated finish

Light Source:

- LED
- Dimming to 10% Included

Notes:

- Mounting Kit Included for standard J-box
- The LCAC has a typical leadtime is minimum 6weeks, consult with factory for any minumum order quanities and setup fees
- UL and CUL listed **DAMP** location
- LED Array
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components
- For a pendant mounted version see the LCAH



Battery Backup Extension ring

Type:	
Job Name:	



Shown with Chocolate Linen Acrylic Side Lens













DIFFUSER OPTIONS






















LCAC-LED





LCAC-19 LCAC-24

DIM 'A'	DIM 'B'	DIM'C'		
19"	8″	12"		
24"	8″	16"		

ORDERING INFORMATION

Example: LCAC-19-LED-F1P-4-W2-CTA-DIM

LCAC

Size	LED					Kelvin	Cage	Diffuser	Diffusers	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		WTA White Textured Acrylic	WLA White Linen Acrylic CTA Chocolate Textured	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v
19-LED	F1L	9	1400	0-10v	YES				Acrylic	See Resource Page
	F10	10	1065	TRIAC/ELV	YES	Ontional			Optional Trim Options	ES Energy Star listed components
	F1P	15	1724	TRIAC/ELV	YES	Optional 3 3500K			(Consult Factory)	90CRI Consult Factory
24-LED	F1K	13	2115	0-10v	YES			1 '	RTA Rapid Textured Acrylic	
	F1P	15	1724	TRIAC/ELV	YES				BTA Black Textured Acrylic	42 Aluminum Pan
	F1Q	23	2540	TRIAC/ELV	YES				Actylic	OCCHFA Concealed Occupancy Sensor
									Bottom Diffuser WTA White Textured Acrylic	See Sensor Resource Sheet
										Battery Backup Options (Requires 1 ¾" extension ring) LCAC-24 only (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes



