

MITW-LED

OUTDOOR LED WALL SCONCE



A clean architectural profile. Built for lasting performance.

A contemporary wall sconce for hospitality, multifamily, retail and office entries. Durable steel construction and a UV-stabilized, high-impact DR acrylic diffuser combine with versatile LED performance.

UL / CUL WET	ADA at 4" depth	0-10V dimming	BABA compliant
--------------	-----------------	---------------	----------------

PERFORMANCE & CONSTRUCTION

120-277V universal voltage; CRI > 90
CCT: 2700K / 3000K / 3500K / 4000K / 5000K
0-10V dimming to 10% included
TRIAC/ELV on qualifying configurations
Field-replaceable LED module; integral driver
Standard 3-step MacAdam binning
Lumen maintenance: > 60,000 hours
Integral mounting plate; hardware included
5-year LED warranty; optional 10-year available

SIZES & OUTPUT

Model / H x W x D	Watts	Source lm
916 / 16" x 9" x 4"	18	2,420
920 / 20" x 9" x 4"	29	4,000
926 / 26" x 9" x 4"	18 / 36	2,420 / 4,840
Mounting centers (M.C.)		
MITW-916: 8" / MITW-920: 10" / MITW-926: 13"		

FINISHES

Standard Satin Black, Textured Black, Anodized Silver, Satin Bronze, Brushed Nickel Powder

Optional Deep Red, Textured Black, Sand Fossi, Brass Powder, Sage Green, Butterscotch, Tuscan Sun, Silver Gray, Pewter, Parker Blue, Cornflower Blue, Textured White, Medium Gray, Antique Brass

Non-VOC powder-coat and low-VOC metal finishing options. Custom finishes: consult factory.

OPTIONS

Photocell (120V or 277V; adds 1 1/2" depth) • All-aluminum construction • J-box with knockouts on all sides (no longer ADA) • Battery backup: 10W / 1,170 lm for 90 minutes; 0-10V only

Application image is illustrative. Dimensions shown are for the standard fixture. Source lumens vary by configuration. Updated to the supplied MITW-LED document; output data from specification sheet revision 03/02/2026. Consult factory for ordering details.