

RBSH-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth polycarbonate
- Optional alabaster acrylic is .080" thick

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights and cage designs available
- Optional battery backup
- Single stem 45-degree swivel standard
- Standard bottom lens is white smooth polycarbonate; optional clear acrylic lens or solid cover
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



RBSH-24

Height - 24 3/4"
Width - 8 1/4"
OAH - 44"

RBSH-36

Height - 37"
Width - 8 1/4"
OAH - 54"



ORDERING INFORMATION

Example: RBSH-24-LED-B-O16B-3-Z3-WSP-WBL-1SLM45-44"OAH

RBSH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O8B	58	8000	0-10v	NO	2 3000K 3 3500K 4 4000K	A B X	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSP White Smooth Polycarbonate	(Suspension Systems) Please list Over All Height 1S45 - Single Stem (Standard) 1SLM45 - Single Stem 45 degree swivel 1S154AC - Single Stem w/Aircraft Cable 4AC__ - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord
	O16B	116	16000	0-10v	NO			W17 Gloss White W18 Gloss White W19 Gloss White W20 Gloss White W21 Gloss White W22 Gloss White W23 Gloss White W24 Gloss White W25 Gloss White W26 Gloss White W27 Gloss White W28 Gloss White W29 Gloss White W30 Gloss White W31 Gloss White W32 Gloss White W33 Gloss White W34 Gloss White W35 Gloss White W36 Gloss White W37 Gloss White W38 Gloss White W39 Gloss White W40 Gloss White W41 Gloss White W42 Gloss White W43 Gloss White W44 Gloss White W45 Gloss White W46 Gloss White W47 Gloss White W48 Gloss White W49 Gloss White W50 Gloss White W51 Gloss White W52 Gloss White W53 Gloss White W54 Gloss White W55 Gloss White W56 Gloss White W57 Gloss White W58 Gloss White W59 Gloss White W60 Gloss White W61 Gloss White W62 Gloss White W63 Gloss White W64 Gloss White W65 Gloss White W66 Gloss White W67 Gloss White W68 Gloss White W69 Gloss White W70 Gloss White W71 Gloss White W72 Gloss White W73 Gloss White W74 Gloss White W75 Gloss White W76 Gloss White W77 Gloss White W78 Gloss White W79 Gloss White W80 Gloss White W81 Gloss White W82 Gloss White W83 Gloss White W84 Gloss White W85 Gloss White W86 Gloss White W87 Gloss White W88 Gloss White W89 Gloss White W90 Gloss White W91 Gloss White W92 Gloss White W93 Gloss White W94 Gloss White W95 Gloss White W96 Gloss White W97 Gloss White W98 Gloss White W99 Gloss White W100 Gloss White	Optional Lens Material (see Price List)	1545 - Single Stem (Standard) 1SLM45 - Single Stem 45 degree swivel 1S154AC - Single Stem w/Aircraft Cable 4AC__ - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord
									Optional Bottom Lens (see Price List)	
36-LED	O8C	72	9680	0-10v	NO			M17 Brass Powder	WBL White Bottom Lens	Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	O16C	143	19360	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

