

ABLW-LED

Construction:

- Steel housing and chassis
- Diffuser is .060" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-box
- Custom cage styles available
- ADA compliant
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



ABLW-15

Height - 15"
Width - 6.5"
Depth - 3.5"

ABLW-27

Height - 27"
Width - 8"
Depth - 3.5"



ORDERING INFORMATION

Example: ABLW-27-LED-O2C-3-Z3-WTP

ABLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
15-LED	O1C13	9	1400	0-10v	NO	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
27-LED	O2C	18	2420	0-10v	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	90CRI Consult Factory OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute
	O2C32	32	3654	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com



Revision: 06/20/2025