

MEFW-600-LED

Construction:

- Steel housing and chassis
- Diffuser is .10 extruded white acrylic
- Aluminum bar stock

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots
- Top and bottom aluminum cover - standard
- Optional photocell (21) increases fixture depth 1 1/2"
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SHOWN WITH THE P2 FINISH

Height - 14.5" - 22" - 30" - 42" - 54"

Width - 6 1/2"

Depth - 4 3/8"



ORDERING INFORMATION

Example: MEFW-654-LED-O4C-4-P2-WSA

MEFW

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
						2 3000K 3 3500K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt 42 All Aluminum <i>Construction</i> ES Energy Star listed components Optional Voltage - 347V Input voltage to 347v Battery Backup Options <i>(Available with 0-10v only)</i> BB10 10 Watts (1170lm) for 90-Minutes
614-LED	F1H	9	1400	0-10v	YES				
	F1P	15	1361	TRIAC/ELV	YES				
622-LED	O2A	12	1600	0-10v	NO				
630-LED	O2C	18	2420	0-10v	NO				
642-LED	O3C	27	3630	0-10v	NO				
654-LED	O4C29	29	3412	0-10v	NO				
	O4C	36	4840	0-10v	NO		Optional <i>(See Price List)</i> M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel		



28435 Industry Drive, Valencia, California 91355
800-325-4448 / 661-257-0286
www.lightwayind.com • sales@lightwayind.com



MEFW-900-LED

Construction:

- Steel housing and chassis
- Diffuser is .10 extruded white acrylic
- Aluminum bar stock

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots
- Top and bottom aluminum cover - standard
- Optional photocell (21) increases fixture depth 1 1/2"
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SHOWN WITH THE P2 FINISH

Height - 14.5" - 22" - 30" - 42" - 54"
 Width - 9"
 Depth - 5 1/4"



ORDERING INFORMATION

Example: MEFW-954-LED-O4C-4-P2-WSA

MEFW

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
914-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt 42 All Aluminum Construction -347V Input voltage to 347v Battery Backup Options <i>(Available with 0-10v only)</i> BB10 10 Watts (1170lm) for 90-Minutes
922-LED	O2C	18	2420	0-10v	NO				
930-LED	O2C	18	2420	0-10v	NO				
	O4A	24	3200	0-10v	NO				
942-LED	O3C	27	3630	0-10v	NO				
954-LED	O4C29	29	3412	0-10v	NO				
	O3C	27	3630	0-10v	NO				
	O4C	36	4840	0-10v	NO				



28435 Industry Drive, Valencia, California 91355
 800-325-4448 / 661-257-0286
 www.lightwayind.com • sales@lightwayind.com



MEFW-1100-LED

Construction:

- Steel housing and chassis
- Diffuser is .10 extruded white acrylic
- Aluminum bar stock

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots
- Top and bottom aluminum cover - standard
- Optional photocell (21) increases fixture depth 1 1/2"
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Height - 14.5" - 22" - 30" - 42" - 54"
 Width - 11 1/4"
 Depth - 6 1/2"

SHOWN WITH THE P2 FINISH



ORDERING INFORMATION

Example: MEFW-1154-LED-O4C-4-P2-WSA

MEFW

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
						2 3000K 3 3500K 4 4000K			
1114-LED	O2A	12	1600	0-10v	NO		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i>
1122-LED	O3C	27	3630	0-10v	NO				21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt
1130-LED	O2C	18	2420	0-10v	NO				
	O4C	36	4840	0-10v	NO				42 All Aluminum Construction
1142-LED	O3C	27	3630	0-10v	NO				-347V Input voltage to 347v
	O6C	54	7260	0-10v	NO				
1154-LED	O4C29	29	3412	0-10v	NO		Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel		Battery Backup Options <i>(Available with 0-10v only)</i> BB10 10 Watts (1170lm) for 90-Minutes
	O4C	36	4840	0-10v	NO				
	O8C	72	9680	0-10v	NO				



28435 Industry Drive, Valencia, California 91355
 800-325-4448 / 661-257-0286
 www.lightwayind.com • sales@lightwayind.com

