

Construction:

- Steel top, bottom and rings
- Diffuser is white textured polycarbonate
- Optional alabaster lenses are acrylic


Lamps:

- LED
- Dimming to 10%

Notes:

- Integral mounting plate for standard "J-Box"
- Mounting orientation is downward
- Optional photocell attaches to wall mounting bracket, specify 120v or 277v
- Optional battery backup, increases depth 1 1/2"
- **Build America, Buy America Act Compliant**
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



ORDERING INFORMATION

Example: JPOW-LED-12-F2B-3-Z1-AHG

JPOW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F2B	12	1180	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter Optional (See Price List) M17 Brass Powder	WTP White Textured Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) Z1 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286
 www.lightwayind.com • sales@lightwayind.com

