

# BWXW-LED

## Construction:

- Steel housing and chassis
- Diffuser is vandal resistant white textured polycarbonate

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup – hardware include
- Optional Photocell (21)
- Optional battery backup BWXW-11
- J-Box with knockouts for surface mount conduit - increases depth to 4"
- ADA compliant
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

<b>Type:</b>	
<b>Job Name:</b>	



### BWXW-9

Height - 8 ½"  
Width - 4 ½"  
Depth - 3 ½"

### BWXW-11

Height - 11"  
Width - 7"  
Depth - 4"



## ORDERING INFORMATION

**Example: BWXW-9-LED-O2A-4-Z1-WTP**

### BWXW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
9-LED	O2A	12	1600	0-10v	NO	2 3000K 3 3500K 4 4000K	<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder <b>P2</b> Brushed Alum <b>P9</b> Brushed Nickel	<b>WTP</b> White Textured Polycarbonate  <b>Optional Lens Material</b> (See Price List) <b>CTP</b> Clear Textured Polycarbonate	<b>DIM</b> LED dimming driver (0 - 10v)  <b>21</b> Photocell - <i>See Notes</i> -01 120 volt -02 277 volt  <b>39</b> J-Box with Knockouts <b>42</b> All Aluminum Construction  <b>Battery Backup Options</b> (Available with 0-10v only) (BWXW-11 only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes	
11-LED	O2A	12	1600	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
www.lightwayind.com • sales@lightwayind.com

