

# PDLW-LED

## Construction:

- Steel housing and chassis
- Bottom lens is white frosted acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Dark sky compliant
- Wall mount only
- Down light only
- ADA Compliant
- Optional **LBC** large box cover to mount to standard extension box
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### PDLW-24-LED

Height - 3"  
Width - 24"  
Depth - 2"

### PDLW-36-LED

Height - 3"  
Width - 36"  
Depth - 2"

### PDLW-47-LED

Height - 3"  
Width - 47"  
Depth - 2"

Mounts to 2 x 4 box/opening oriented to match fixture's linear dimension



## ORDERING INFORMATION

Example: **PDLW-36-LED-O3C-4-T4-WSA**

### PDLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WFA White Frosted Acrylic	LBC Large box cover standard junction box (5" wide x 6" high)  DIM LED dimming driver (0 - 10v)
36-LED	O3C	27	3630	0-10v	NO					
47-LED	O4C	36	4840	0-10v	NO					
								Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel		Battery Backup Options BB10 Battery backup unit providing 8 Watts (1170lm) for 90-Minute



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

