

RMTW-LED

Construction:

- Steel chassis; aluminum deco trim
- Diffuser is white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



RMTW-7-LED

Height - 7"
Width - 14"
Depth - 4"



ORDERING INFORMATION

Example: RMTW-7-LED-01B-4-Z1-WSA

RMTW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black Z1 Satin Bronze Z3 Textured Bronze T6 Pewter W13 Pearl Beige Optional Finishes (see Price List) T2 Hammerd Copper T3 Hammer Silver T4 Shimmer Gray T5 Textured Silver	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) Optional Voltage - 347V Input voltage to 347v
7-LED	01B	8	1000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com

