

PDSW-LED-AMBER

Construction:

- Aluminum housing and chassis

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**
- Optional 8-watt amber LED

Notes:

- Center lockup – hardware include
- Optional J-Box with knockouts for surface conduit (39)
- Dark sky compliant
- ADA Compliant, Except PDSW-18
- Optional Battery Backup increases depth to 4"
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - Optional Amber LED Module designed for Turtle Spectrum (585-595nm)
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

PDSW-5-LED PDSW-12-LED

Height - 5 1/8" Height - 5 1/8"
 Width - 7 1/8" Width - 12"
 Depth - 3 1/2" Depth - 3 1/2"

Type:	
Job Name:	



*Shown with
Amber arrays*



ORDERING INFORMATION

Example: PDSW-5-LED-U-AMR8W-B1-CPA

Model	Cage	Voltage	Lamping	Finish	Diffuser	Options
PDSW-5-LED		U 120 - 277	AMR-8w LED / 357lm	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze	WFA White Frosted Acrylic CPA Clear Prismatic Acrylic WTA White Textured Acrylic CSA Clear Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) DIMLD LED Phase dimming driver (120 Volt Only) 39 J-Box with Knockouts (increases depth by 1 1/4") TP Tamper Proof Screws UP/DN Damp listing only (Up/Down Light) Battery Backup Options (Increases fixture depth to 4") BB10 10 Watts for 90-Minutes
PDSW-12-LED			AMR-8w LED / 357lm	Optional (See Price List) M2 Copper Melallic W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass		



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com

