

PMRC-LED

Construction:

- Steel pan
- Diffuser is white smooth acrylic
- Optional diffusers are alabaster smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box installation
- Optional battery backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PMRC-17-LED	PMRC-21-LED	PMRC-24-LED	PMRC-36-LED
Height - 7 1/2"	Height - 9"	Height - 10-1/2"	Height - 10-1/2"
Width - 16 1/2"	Width - 20 3/4"	Width - 24"	Width - 36"



ORDERING INFORMATION

Example: **PMRC-17-LED-F1Q-4-T4-BAA**

PMRC

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
17-LED	F1L	9	1400	0-10v	YES	2 3000K 3 3500 4 4000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1K	13	2115	0-10v	YES			Z1 Satin Bronze		
	F1P	15	1361	TRIAC/ELV	YES			W1 Yolk White		
	F1Q	23	2057	TRIAC/ELV	YES			W2 Gloss White		
21-LED	F1K	13	2115	0-10v	YES			T4 Shimmer Gray	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	ES Energy Star listed components T24 Title 24/JA8 Compliant (F1P & F1Q configuration only)
	L1A	36	4000	0-10v	NO			M13 Anod Silver		
	F1P	15	1361	TRIAC/ELV	YES			T6 Pewter		
	F1Q	23	2057	TRIAC/ELV	YES			W13 Pearl Beige		
24-LED	O8C	72	9680	0-10v	NO			Optional (See Price List)	OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet	Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
36-LED	O12C	107	14520	0-10v	NO		M17 Gold Brass P9 Brushed Nickel			



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

