

# DKBW-LED

## Construction:

- Steel housing, chassis and cage
- Shield design offset from lens
- Diffuser is .10" thick extruded acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Integral mounting plate; keyhole slots left and right
- Top and bottom white acrylic lens- standard
- Optional photocell (21) increases fixture depth 1 ½"
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Integral Power Supply
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



<b>DKBW-10</b>	<b>DKBW-16</b>	<b>DKBW-22</b>	<b>DKBW-26</b>
Height - 10"	Height - 16"	Height - 22 ¼"	Height - 26 ½"
Width - 9"	Width - 9"	Width - 9"	Width - 9"
Depth - 6"	Depth - 6"	Depth - 6"	Depth - 6"



## ORDERING INFORMATION

**Example: DKBW-26-LED-F4D-4-B1-WSA-DIM**

### DKBW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
<b>10-LED</b>	<b>F4D</b>	48	4384	0-10v	NO	2 3000K 3 3500K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige	<b>WSA</b> White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v)
<b>16-LED</b>	<b>F4D</b>	48	4384	0-10v	NO					<b>21</b> Photocell - Specify voltage 01 - 120 volt 02 - 277 volt
<b>22-LED</b>	<b>F4D</b>	48	4384	0-10v	NO					<b>42</b> All Aluminum Construction
<b>26-LED</b>	<b>F4D</b>	48	4384	0-10v	NO					Optional Voltage <b>-347V</b> Input voltage to 347v
										<b>Battery Backup Options</b> (Available with 0-10v only) <b>(Excludes DKBW-10)</b> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
								<b>Optional</b> (See Price List) <b>M17</b> Brass Powder <b>P2</b> Brushed Alum <b>P9</b> Brushed Nickel		



28435 Industry Drive., Valencia, California 91355  
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
www.lightwayind.com • sales@lightwayind.com

